

BUILT TO RENT

Portable Compressors

Mobilair™ M122



Tough, Dependable Unit

The Mobilair™ M122 is a versatile unit suited for a number of applications including sand-blasting, pavement breaking, and general air tool use. Units are also well suited for rental houses, repair trucks, and railroads.

The M122 offers a wide array of features that make it very user-friendly. Units come standard with an easy to read control panel that is well protected. The fuel tank has a large filler neck with overflow protection for safe, easy filling. A hitch and rigid tow bar also make transporting the M122 easy. A torsion

bar suspension system and oversized tires provide superior road handling, further adding to the unit's exceptional functionality.

Unsurpassed Durability and Quietness

The M122's heavy duty steel chassis and fully galvanized canopy ensure smooth operation even when subjected to the harshest conditions. Both the canopy and solid steel flooring protect the motor, airend, and critical components from dirt, water, and other contaminants. This rugged construction

Standard Features:

- Rotary screw airend: Sigma profile produces more air with less fuel consumption
- Heavy duty steel chassis
- Fully galvanized canopy
- 1 micron, 2-stage compressor inlet filter with maintenance indicator
- 10 micron engine air filter with maintenance indicator
- High capacity cold start battery ensures reliable operation even under extreme working conditions
- Heavy duty diesel engine complies with Tier 3 emissions standards
- Tool boxes for convenient storage
- Lifting eye for simple handling
- Highly efficient cooling system
- Modulation control

Optional Features:

- Pressures to 205 psig
- Aftercooler and filtration packages
- Five year airend warranty
- Skid mount
- Hose reels and gauge packages
- Complete line of air tools

combined with extensive engineering allow the M122 to operate in ambient temperatures up to 122°F. The canopy is also super soundproofed and provides extremely low decibel levels. Maximum sound level measured at 23 feet is only 76 db(A).

Features and Benefits



Air Filter

10 micron engine air filter and 1 micron, 2-stage compressor inlet filter both with maintenance indicator



Oil Filter

10 micron spin-on oil filter with integrated thermostatic valve



Fuel Tank

Large capacity fuel tank provides 8 hours of operation



Airend

Efficient Sigma Profile rotary screw airend produces more air with less fuel consumption.



Skid mount option

Control Panel



Easy to read control panel is well protected

Specifications

Compressor		Diesel Engine		Package		Dimensions (in.)	
Free air delivery	400 cfm	Make	Deutz TCD2012 L4	Fuel tank capacity	45 gal.	Length*	186
Working Pressure	100 psig	Power at full load	103.3 hp	Weight, dry	3790 lb.	Width	73
		Full load speed	2300 rpm	Outlets	3 x 3/4"; 1 x 1 1/2"	Height	63
		Off load running speed	1600 rpm	Sound level max	76 db(A) at 23 ft.	*includes tow bar	

Specifications are subject to change without notice.

KAESER COMPRESSORS

Built for a lifetime.™

www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Verendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda.
Calzada Atanasio Tzul 21-00,
Zona 12, Complejo Empresarial
El Cortijo II, Bodega 501
01012 Guatemala
Telephone: +502 2412-6000
info.guatemala@kaeser.com

Certified Management Systems

